Quick Specs

AlumaView® AV300

1.1 MANUFACTURERS

A. Acceptable Manufacturer: Raynor, which is located at: 1101 East River Rd. P. O. Box 448 ; Dixon, IL 61021-0448; Toll Free Tel: 800-4-RAYNOR; Tel: 815-288-1431; Fax: 888-598-4790; Email: request info (thegarage@raynor.com); Web: www.raynor.com

1.2 SECTIONAL RAIL AND STYLE ALUMINUM DOORS

A. AlumaView as manufactured by Raynor Garage Doors:
   1. Doors:
      a. Operation (select from list below):
         1) Provide doors designed for manual operation.
         2) Provide doors designed for hand chain operation.
         3) Provide doors designed for electric motor operation.
      b. Jamb Construction (select from list below):
         1) Steel jambs with self-tapping fasteners.
         2) Wood jambs with lag screw fasteners.
         3) Masonry jambs with anchor bolt fasteners.
      c. Structural Performance Requirements (insert required wind load psf):
         1) Wind Loads: Uniform pressure of: _____ psf.
   2. Sections:
      a. AlumaView AV300:
         1) Material: 3 inches (76 mm) thick, 6063-T6 aluminum alloy stiles and rails joined together with 5/16 inch (8 mm) diameter screws. Aluminum panels 0.050 inch (1.3 mm) thick or glazing (when specified) fill the spaces between stiles and rails. Combined dimension of two adjoining intermediate meeting rails 5 inches (127 mm). Bottom rail height 6-1/2 inches (165 mm). Top rail height 6-1/2 inches (165 mm). End stiles 3-3/8 inches (86 mm) or 6-1/2 inches (165 mm) wide as determined by overall door width. Center stiles 3-5/8 inches (92 mm) wide.
         2) Finish: Aluminum frame extrusions and filler panels finish coated (select from list below):
            a) Color: Clear anodized finish.
            b) Color: Champagne anodized finish.
            c) Color: Light Bronze anodized finish.
            d) Color: Medium Bronze anodized finish.
            e) Color: Dark Bronze anodized finish.
            f) Color: Extra Dark Bronze anodized finish.
            g) Color: Black anodized finish.
            h) ArmorBrite Powdercoat finish.
               1) Color: _____.
      b. Seals: Bottom of door to have flexible U-shaped vinyl seal retained in aluminum rail (select from list below):
         1) Bulb-type joint seal between sections.

2) Blade seal on top section to prevent airflow above header.

c. Trussing: Doors designed to withstand specified wind load. Deflection of door in horizontal position to be maximum of 1/120th of door width.

3. Windows: Provide door sections with windows in lieu of 0.050 inch (1.3mm) aluminum filler panels. Locations to comply with door elevation drawings (select from list below):

4. Glazing: Windows to be provided as follows (select from list below):
   a. 1/8 inch (3.2mm) Clear Glass consisting of one pane of 1/8 inch (3.2mm) DSB non-insulated glass.
   b. 3/16 inch (4.8mm) Clear Glass consisting of one pane of 3/16 inch (4.8mm) non-insulated glass.
   c. 1/4 inch (6.4mm) Clear Glass consisting of one pane of 1/4 inch (6.4mm) non-insulated glass.
   d. 1/8 inch (3.2mm) Clear Tempered Glass consisting of one pane of 1/8 inch (3.2mm) non-insulated glass.
   e. 1/4 inch (6.4mm) Clear Tempered Glass consisting of one pane of 1/4 inch (6.4mm) non-insulated glass.
   f. 3/16 inch (4.88mm) Clear Tempered Glass consisting of one pane of 3/16 inch (4.88mm) non-insulated glass.
   g. 1/4 inch (6.4mm) Clear Laminated Glass consisting of one pane of 1/4 inch (6.4mm) non-insulated glass.
   h. 1/4 inch (6.4mm) Clear Wire Glass consisting of one pane of 1/4 inch (6.4mm) non-insulated glass.
   i. 1/8 inch (3.2mm) Tinted Glass consisting of one pane of 1/8 inch (3.2mm) non-insulated glass.
   j. 1/4 inch (6.4mm) Tinted Glass consisting of one pane of 1/4 inch (6.4mm) non-insulated glass.
   k. 1/8 inch (3.2mm) Tinted Tempered Glass consisting of one pane of 1/8 inch (3.2mm) non-insulated glass.
   l. 1/4 inch (6.4mm) Tinted Tempered Glass consisting of one pane of 1/4 inch (6.4mm) non-insulated glass.
   m. 1/2 inch (12.69mm) Insulated Clear Glass consisting of two panes of 1/8 inch (3.2mm) DSB insulated glass.

5. Mounting: Sections mounted in door opening using (select from list below):
   a. Between-Jamb Bracket Mounting: sections mounted between door jambs, seal against exterior perimeter seal installed along vertical and top horizontal edges of jambs.
   b. Lap Jamb Angle Mounting: section overlap door jambs by 1 inch (25 mm) on each side of door opening.

6. Track:
   a. Material: Hot-dipped galvanized steel (ASTM A 653), fully adjustable for adequate sealing of door to jamb or weatherseal.
   b. Configuration Type (select from list below):
      1) Configuration Type: Normal Headroom.
      2) Configuration Type: Low Headroom.
      3) Configuration Type: Vertical Lift.
      4) Configuration Type: Lift-Clearance.
      5) Configuration Type: Incline.
      6) Configuration Type: Contour.
   c. Track Size (select from list below):
      1) Size: 2 inches (51 mm).
      2) Size: 3 inches (76 mm).
   d. Mounting (select from list below):
      1) Bracket-Mount using adjustable track brackets for use on 2-inch track with wood jambs.
      2) Floor-to-Header Angle-Mount consisting of continuous angle

extending from the floor up to the door header for use with steel, wood, or masonry jambs. Continuous angle size not less than 2-5/16 inches by 4 inches by 3/32 inch (59 by 102 by 2.5 mm) on 2-inch track and 3-1/2 inches by 5 inches by 1/8 inches (89 by 127by 3.2 mm) on 3-inch track.

3) Floor-to-Shaft Angle-Mount consisting of continuous angle extending from the floor, past header, completely up to door shaft for use with steel, wood, or masonry jambs. Continuous angle size not less than 2-5/16 inches by 4 inches by 3/32 inch (59 by 102 by 2.5 mm) on 2-inch track and 3-1/2 inches by 5 inches by 1/8 inches (89 by 127by 3.2 mm) on 3-inch track.

e. Finish (select from list below):
   1) Galvanized.
   2) White Powdercoat.

7. Counterbalance:
   a. Counterbalance System: Provided with aircraft-type, galvanized steel lifting cables with minimum safety factor of 5. Torsion Springs consisting of heavy-duty oil-tempered wire torsion springs on a continuous ball-bearing cross-header shaft. Specify cycle life below (up to 200,000)
      1) Spring Cycle Requirements: Standard 10,000 cycles.
      2) Spring Cycle Requirements: High cycle: _____ cycles.
8. Hardware (specify rollers below):
   a. Hinges and Brackets: Fabricated from galvanized steel.
   b. Track Rollers: 2 inches (50.8 mm) diameter consistent with track size, with hardened steel ball bearings.
   c. Track Rollers: 3 inches (76.2 mm) diameter consistent with track size, with hardened steel ball bearings.
   d. Perimeter Seal (optionally provided): Provide complete weather stripping system to reduce air infiltration. Weather stripping shall be replaceable.
      1) For bracket mounted doors provide climate seal or vinyl seal with aluminum retainer.
      2) For angle mounted doors provide angle clip-on seal.
   e. Furnish door system with locks (optionally provided): Exterior lock with five-pin tumbler cylinder, night latch and steel bar engaging track.
   f. Furnish door system with locks (optionally provided): Interior lock with dead bolt provided with hole to receive padlock provided by Owner.
9. AlumaView Limited Warranty: Raynor warrants the door sections against defects in material and workmanship for five years from date of delivery to the original purchaser. Window components are warranted against defects in material and workmanship for three years from date of delivery to the original purchaser. Raynor warrants all hardware and spring components against defects in material and workmanship for one year (or cycle life of the springs) from date of delivery to the original purchaser. Additional Limited Warranty requirements in accordance with manufacturer's full standard limited warranty documentation.