

DC BATTERY BACKUP BELT DRIVE WI-FI® GARAGE DOOR OPENER

FEATURE RICH, OFFERING ULTIMATE GARAGE PROTECTION.



AUTOMATIC GARAGE DOOR LOCK CAPABLE: DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

TIMER-TO-CLOSE CAN BE PROGRAMMED TO CLOSE THE DOOR AFTER A SET AMOUNT OF TIME.

SECURITY+ 2.0° SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ*.

MOTION DETECTOR LIGHTS THE WAY AUTOMATICALLY.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

BELT DRIVE SYSTEM FOR POWERFUL, ULTRA-QUIET PERFORMANCE.

SOFT START/STOP FOR SMOOTH OPERATION.

DC MOTOR IS PURPOSEFULLY DESIGNED FOR QUIET, LONG-LASTING SERVICE.

BATTERY BACKUP ENSURES GARAGE ACCESS EVEN WHEN THE POWER IS OUT.

WARRANTY LIFETIME MOTOR AND BELT, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

FREE MYQ MOBILE APP SO USERS KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

INCLUDED ACCESSORIES:

Smart Control Panel®

LCD display enables simple programmming and adjustment of settings.



3-Button Remote Control

Operates up to 3 openers or MyQ Light Accessories.



2220178

Integrated Battery Backup Powers up the opener when the power is out.



6080759

POWERFUL ADD-ONS:

Automatic Garage Door Lock Capable

Deadbolts the garage door automatically every time it closes.



Remote Light Control

Plug in any lamp to this device to control it with a smartphone or garage remote.



Mini Universal Remote Control Compact and portable to provide quick, easy garage access.



MyQ Remote LED Light

Provides convenient, secure access from outside the garage with a 4-digit PIN.



6081024

Admiral II[®] with WiFi[®]



MASTERFUL ENGINEERING.

MOTOR



- 12V DC

MECHANICS

- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

Environmental Conditions - **Electronic Limits** for Easy Setup

- Steel Chassis, T-Rail and Trolley

Reduction and Adjustable Door Arm)

- Full Reinforced Belt Drive Mechanism (63:1 Gear

- Auto-Force Adjustment for Changing Weather and

- DC WiFi® Logic Board with Built-In Surge Suppressor

(for Replacement Logic Boards, Order Part 050DCTWFLK)

Operating Range:

- 2 Lock Terminals Allow up to 2 Locks to Be Connected

POWER



- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed

- 120V AC

- 6' Power Cord (3-Prong)



my@

DIMENSIONS

Rail Options	7'	81	10'
Installed Length	125"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

Per second for door to move

upward

SPEED

Per second for door to move downward

STANDARD SPECS.

(Sold Separately)

SECURITY+ 2.0°

RADIO CONTROLS Operating

Temperature: -40°F to 150°F


- 3-Button Remote Control
- Remote Control: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding
- *Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

Smart Control Panel®

- Timer-to-Close
- Program Remote controls, Keypads and MyQ Accesories
- Maintenance Alert System
- Easy WiFi® Setup

MyQ° RADIO



(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

LIGHTING





- Max. 2 100-Watt Lightbulbs
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts
- Disabled in Battery Backup Mode

SHIPPING.

SHIPPING WEIGHT (in lbs.) **CARTONS (4)**

CARTON 1: 20" x 12" x 10"

- Garage Door Opener Head
- Smart Control Panel
- 3-Button Remote Control
- The Protector System® Safety Reversing Sensors
- CARTON 2: 10'4" x 5" x 5" (for 7' Rail)
- Assembled Solid-Steel Belt T-Rail





BATTERY BACKUP



AUTOMATIC GARAGE DOOR LOCK (OPTIONAL)

CARTON 3: 5.31" x 4.63" x 5.13"

CARTON 4 (OPTIONAL): 8" x 4.5" x 4"

- Automatic Garage Door Lock

SAFETY AND SECURITY.

- Automatic Garage Door Lock Capable (2 Max.)
- Alert-2-Close/Unattended Close Operation[†]
- Motion Detection Feature on Control panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening

- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 MyQ Devices

HomeLink" and the HomeLink House" logo are registered trademarks of Gentex Corporation

t: to reduce the risk of injury to persons, only use alert-2-Close/Unattended Close Operation features when installed with a sectional door.



