

1/2 HP AC BELT DRIVE GARAGE DOOR OPENER

DEPENDABLE PERFORMANCE



WARRANTY

- 4-YEAR**
Motor

- 1-YEAR**
Parts & Accessories

- 10-YEAR**
Belt

RELIABLE



1/2 HP AC MOTOR WITH INDUSTRIAL-STRENGTH BELT DRIVE SYSTEM PROVIDES RELIABLE AND MAINTENANCE FREE PERFORMANCE.

ENERGY-EFFICIENT OPERATION CONSUMES UP TO 75% LESS POWER IN STANDBY MODE.

SMART



MyQ TECHNOLOGY ENABLES YOU TO SECURELY MONITOR AND CONTROL YOUR GARAGE DOOR OPENER AND HOUSELIGHTS WITH YOUR SMARTPHONE, TABLET OR COMPUTER.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

SECURE

Security+ 2.0®

SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK SO YOUR DOOR OPENS ONLY FOR YOU.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

INCLUDED ACCESSORIES:

1-Button Remote Control

Allows you to control a single garage door opener, gate operator or MyQ Light Accessory.



2220181

891 RGD

Multi-Function Control Panel

Allows you to program remote controls, keypads and MyQ Accessories from the control panel. Includes lockout remote controls for added security.



6080979

882 WRGD

POWERFULL ADD-ONS:

Internet Gateway

Connects your MyQ-Enabled Garage Door Opener and Accessories to the Internet with this device and the free MyQ app.



2220170

828 LM

Remote Light Control

Enables home lighting control through a garage remote or a smartphone.



2220174

825 LM

MASTERFUL ENGINEERING.

MOTOR

- ½ Horsepower
- 1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 5.0A Current Rating
- UL Listed
- 4' Power Cord (3-Prong)

MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **Solid State Microcontroller** with Built-In Surge Suppressor



DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	124"	136"	160"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

7"

Per second for door to move upward

SPEED

7"

Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®

RADIO CONTROLS

3-Button Remote Control (893 RGX)

Operating Range: ~200'

Operating Temperature: -40°F to 150°F

- Remote Control: 310, 315 and 390 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 310, 315, 390 MHz
- Security+ 2.0 Anti-Burglary Coding

SECURITY +2.0 ENCRYPTED CONTROLS

Multi-Function Control Panel*

- Program Remote Controls
- Maintenance Alert System

SMART

MyQ® RADIO

902-928 MHz

50-Channel FHSS

(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables remote closing of garage door with key MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

ELECTRICAL

LIGHTING



- Max. 100-Watt Light bulbs
- 4½ minute Solid-State light delay
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

ENERGY EFFICIENCY

- Approximately 1 Watt Power in Standby mode*

*Occurs at Down Limit When opener's Lights Turn Off

SHIPPING.

SHIPPING WEIGHT (in lbs.)

CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Multi-Function Control Panel
- 1-Button Remote Control
- Garage Door Opener Head
- The Protector System®

CARTON 2: 10'4" x 5" x 5"

- Assembled Solid-Steel T-Rail



CONVENIENCE AND SAFETY.

- The Protector System® Safety Reversing Sensors
- Alert-2-Close/Unattended Close Operation†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Door Open/Beam obstructed/Lights On
- Maintenance alert System
- Garage Door Opener Capacity of up to 24 Remote Controls, 2 Wireless Keyless Entry Systems and 16 MyQ Devices
- PosiLock® Secure Lock System



HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation

†: To reduce the risk of injury to persons, only use alert-2-Close/Unattended Close Operation features when installed with a sectional door.